

ABSPIN PLUS CENTRIFUGE XC-3000台式低速离心机

广泛应用于医疗机构、生物化学实验室、美容院等，对样品进行分离的必备设备。

LabSpin plus is the most powerful and competitive centrifuge in its class, can be placed 6 of 15ml conical tubes or glass tubes, 8 of 15ml conical tubes or glass tubes conical tubes which with screw caps. The speed can be 500- 5000RPM, LCD display, with ability to change between RPM and RCF. The centrifuge is ideal for the separation of serum plasma, urea, blood samples and other routine applications in hospital and research laboratories.

技术性能 | Features

- 微机控制，电动电机。
Microcomputer control, Electric motor, Silent, constant, stable and high speed accuracy.
- 触摸按键，运行中参数可根据需求设置。
Touch button, The parameter can be set according to demands during operation and stored automatically.
- 液晶显示，可实时切换rpm/RCF之间的读数。
LCD screen which can display the speed, centrifugal force and time in real time at the same time. It can switch the reading between rpm/RCF in real time.
- 机壳彩用ABS注塑一次成形，外观简洁、体积轻巧、噪音低。
ABS Outlook injection molding at one time, with simple appearance, light volume and low noise.
- 配有电子门锁，设有门盖、超速保护，具有故障自动报警功能，安全可靠。
Lid safety device, with Lid, over-speed protection system, automatic fault alarm function, safe and reliable. Safety-Lock lid, which ensures a safe, tight closure on the centrifuge chamber during operation. Electronic lock and emergency lid release are available.

技术参数 | Specification

型号Model	XC-3000
最高转速(角式) Max. Speed	500~5000r/min
最大相对离心力(角式) Max. RCF	3074×g
最大容量Max. Capacity	12×10ml
转速精度Speed Accuracy	±10r/min
定时范围Time Range	10s-99min59s
整机噪声Noise	≤ 50dB(A)
电源Voltage Supply	AC220V/ 50Hz/ 5A (OR AC110V)
整机功率Power	40W
外形尺寸Dimension (mm)	375x320x240 mm(L×W×H)
重量Weight (kg)	5.5KG



转子参数 | Rotor

No.1		No.1	
名称: 角转子 (Angle rotor)	容量 Capacity: 6×15ml	名称: 角转子 (Angle rotor)	容量 Capacity: 8×15ml
最高转速Speed: 5000 (r/min)	最大离心力RCF: 3074×g	最高转速Speed: 5000 (r/min)	最大离心力RCF: 3074×g
No.2		No.2	
名称: 角转子 (Angle rotor)	容量 Capacity: 12×10ml	名称: 角转子 (Angle rotor)	容量 Capacity: 12×5ml
最高转速Speed: 4000 (r/min)	最大离心力RCF: 2220×g	最高转速Speed: 4000 (r/min)	最大离心力RCF: 2220×g

SPIN CENTRIFUGE L-50台式低速离心机

广泛应用于医疗机构、生物化学实验室、美容院等，是对样品进行分离的比配设备。

XC-2000 Spin centrifuge is used in laboratory, hospitals, colleges and universities. Clinician centrifuge are single and variable speed respectively. They are designed to fulfill basic centrifugation requirements with the capacity to spin 6 x 10ml or 15ml tubes.

技术性能 | Features

- 微机控制，电动电机。
Microcomputer control, Electric motor, Silent, constant, stable and high speed accuracy.
- 机壳彩用ABS注塑一次成形，外观简洁、体积轻巧、噪音低。
ABS Outlook injection molding at one time, with simple appearance, light volume and low noise.
- 设有门盖、超速保护，具有故障自动报警功能，安全可靠。
Lid safety device, with Lid, over-speed protection system, automatic fault alarm function, safe and reliable.

技术参数 | Specification

型号Model	L-50
最高转速(角式) Max. Speed	4000r/min
最大相对离心力(角式) Max. RCF	1790×g
最大容量Max. Capacity	6×15m (105mm) 6×15m (110mm)
转速精度Speed Accuracy	±30r/min
定时范围Time Range	1min-99min
整机噪声Noise	≤ 65dB(A)
电源Voltage Supply	AC220V/ 50Hz/ 5A (OR AC110V)
整机功率Power	40W
外形尺寸Dimension (mm)	270x275x275(L×W×H)
重量Weight (kg)	5KG

转子参数 | Rotor

No.1	
名称: 角转子 (Angle rotor)	容量 Capacity: 6×15ml(110mm)
	6×15ml(105mm)
最高转速Speed: 4000 (r/min)	最大离心力RCF: 1790×g

