

PRP/SYRINGE MULTI-FUNCTION FAT CENTRIFUGE LC-530美容专用 (PRP脂肪注射移植) 离心机

LC-530多功能脂肪及PRP干细胞提纯离心机，可专业用于脂肪提纯和PRP提纯；使用10ml、20ml、50ml、60ml常规注射器，快速分离提纯脂肪和PRP，为提高脂肪的成活率，我司在离心转速、时间、离心力、直径等方面做了大量研究，研制出专业脂肪移植和PRP移植的多功能提纯离心机，提高了手术效率，缩短了手术时间，最大程度地提高了手术中的脂肪及PRP的成活率，使移植手术简单便捷，是整形医生首选的最佳助手。

Multi-function fat and stem cells purified PRP centrifuge, fat can be purified and used for professional PRP purification; use 10ml, 20ml, 30ml, the conventional syringe. Rapid separation and purification of fat and PRP, to improve the survival rate of fat in the centrifuge speed, time, centrifuge force, diameter, so a lot of research, developed a specialized fat grafting and transplantation of the multi-purpose centrifuge purification, as the skin is autologous blood Health and surgical technique improve the efficiency, shorten the operation time, maximize the surgery in the survival rate of the fat and the PRP, the transplant operation simple and convenient, plastic surgeon is the most preferred.

技术性能 | Features

- 微机控制，高效能变频电机。
Microcomputer control, DC Frequency motor, Silent, constant, stable and high speed accuracy.
- 单旋钮按键，运行中参数可根据需求设置。
Single knob button, parameters can be set according to demands during operation and stored automatically.
- LCD液晶屏，同时可实时显示转速、离心力和时间等数值。
LCD screen which can display the speed, centrifugal force and time in real time at the same time.
- 机壳彩用ABS注塑一次成形，外观简洁、体积轻巧、噪音低。
ABS Outlook injection molding at one time, with simple appearance, light volume and low noise.
- 配有电子门锁，设有门盖、超速保护，具有故障自动报警功能，安全可靠。
Lid safety device, with Lid, over-speed protection system, automatic fault alarm function, safe and reliable. Safety-Lock lid, which ensures a safe, tight closure on the centrifuge chamber during operation. Electronic lock and emergency lid release are available.
- 10档升/降速运行模式。
10 programs of acceleration and deceleration level for your choice.

技术参数 | Specification

型号Model	LC-530
最高转速Max. Speed	4200r/min
最大相对离心力Max. RCF	4900×g
最大容量(水平式) Max. Capacity	4×60ml (一次性注射器)
转速精度Speed Accuracy	±10r/min
定时范围Time Range	10s-9h59min59s
整机噪声Noise	≤ 65dB(A)
电源Voltage Supply	AC220V/ 50Hz/ 10A (OR AC110V)
整机功率Power	550W
外形尺寸Dimension (mm)	580×470×355mm(L×W×H)
重量Weight (kg)	35KG



转子参数 | Rotor

<p>No.1</p>  <p>名称: 水平转子 (Horizontal rotor) 容量 Capacity: 2×8×15ml+ 2×50/60ml 适配器: 5ml/10ml 最高转速Speed: 4200 (r/min) 最大离心力RCF: 4900×g</p>	<p>No.2</p>  <p>名称: 水平转子 (Horizontal rotor) 容量 Capacity: 4×60ml 最高转速Speed: 4200 (r/min) 最大离心力RCF: 4900×g</p>	<p>No.3</p>  <p>名称: 适配器 (Adaptor) 容量 Capacity: 50/60ml注射器 用于: 4×50ml</p>	<p>No.4</p>  <p>名称: 适配器 (Adaptor) 容量 Capacity: 30 ml注射器 用于: 4×50ml</p>	<p>No.5</p>  <p>名称: 适配器 (Adaptor) 容量 Capacity: 20 ml注射器 用于: 4×50ml</p>
<p>No.6</p>  <p>名称: 适配器 (Adaptor) 容量 Capacity: 10 ml注射器 用于: 4×50ml</p>	<p>No.7</p>  <p>名称: 适配器 (Adaptor) 容量 Capacity: 10/5mlPRP采血管 用于: 4×50ml</p>	<p>No.8</p>  <p>可适用于多种PRP管</p>		