

PG SPINPLUS (PRF /CGF) CENTRIFUGE **L-400台式低速(CGF)离心机**

专用性程序设置，一键式操作，可同时使用12个试管制备CGF（血纤维蛋白），一机三模式，PRP, PRF, CGF口腔种植CGF离心机（变速离心机），具有高低速转速变化的离心系统，可将骨再生所需要的各种生长因子高度浓缩在CGF中。

Professional programs Setting, One button -touch operation for making 8 of platelet rich fibrin(PRF)or concentrate growth factors(CGF)clot at the same time. One machine for 2 modes "PRF" "CGF". Microprocessor control offer the machine controlled acceleration automatic.

✍ 技术性能 | Features

- 微机控制，电动电机。
Microcomputer control, Electric motor, Silent, constant, stable and high speed accuracy.
- 触摸按键，液晶显示。
Touch button, LCD display.
- 预设4个离心程序，用户可一键调用。
There are 4 preset centrifugation programs, which can be invoked by the user with one button.
- 机壳彩用ABS注塑一次成形，外观简洁、体积轻巧、噪音低。
ABS Outlook injection molding at one time, with simple appearance, light volume and low noise.
- 配有电子门锁，设有门盖、超速保护，具有故障自动报警功能，安全可靠。
Equipped with electronic door lock, door cover, over-speed protection system, automatic failure alarm function, safe and reliable.

✍ 技术参数 | Specification

型号Model	L-400
最高转速（角式）Max. Speed	500~4000r/min
最大相对离心力（角式）Max. RCF	2200×g
最大容量Max. Capacity	12×10ml
转速精度Speed Accuracy	±30r/min
定时范围Time Range	10s-99min59s
整机噪声Noise	≤ 55 dB(A)
电源Voltage Supply	AC220V/ 50Hz/ 5A (OR AC110V)
整机功率Power	80W
外形尺寸Dimension (mm)	375×320×240mm(L×W×H)
重量Weight (kg)	5.5KG



✍ 转子参数 | Rotor

No.1

名称：角转子 (Angle rotor)
容量 Capacity: 6×15ml
最高转速Speed: 4000 (r/min)
最大离心力RCF: 2200×g

No.1

名称：角转子 (Angle rotor)
容量 Capacity: 8×15ml
最高转速Speed: 4000 (r/min)
最大离心力RCF: 2200×g

No.2

名称：角转子 (Angle rotor)
容量 Capacity: 12×10ml
最高转速Speed: 4000 (r/min)
最大离心力RCF: 2220×g

No.2

名称：角转子 (Angle rotor)
容量 Capacity: 12×5ml
最高转速Speed: 4000 (r/min)
最大离心力RCF: 2220×g